

Case Study

Pocan[®] B 4215 for surge arresters



Figure 1 Surge arrester DEHNguard[®] M TT 275 FM made from Pocan[®] B 4215

Lightning is formed in thunderclouds when strong upcurrents of air separate positive and negative charges, leading to an electrical discharge – commonly known as lightning. Every square kilometer in Germany is struck by lightning on average four times a year, an annual total of around one million lightning strikes. In fact, each year lightning causes millions of euros worth of damage and frequently even results in personal injury or death. Before lightning discharges, voltages equal to several 100 million volts occur between the thunderclouds and the earth. In a fraction of a second, currents can be generated which, in rare cases, can amount to several 100,000 A.

DEHN + SÖHNE GmbH + Co. KG, have been developing products for lightning protection, surge protection and grounding since the 1920s. The family-run company has developed two product series,

Red/Line and Yellow/Line, providing perfectly matched surge protection devices. The Red/Line series from DEHN + SÖHNE includes protection devices for installation in switchgear, meter stations, distributors, cable ducts, sockets and terminals. All materials used in these products are subject to very strict requirements.

The same applies to Pocan[®] B 4215 from LANXESS Deutschland GmbH, which is characterized by the following outstanding properties:

- Fire properties
Pocan[®] B 4215 is classified as V-0 to UL 94 V. Classification 5VA is even possible with wall thicknesses greater than 3.5 mm. It also achieves the highest possible GWFI (glow wire flammability index) value of 960 °C.
- Electrical properties
Pocan[®] B 4215 achieves the highest possible HAI ranking (high amp arc ignition) with PLC classification 0.
- Long-term thermal stability
Even with the thinnest walls, RTI (relative temperature index) values are ≥ 130 °C. The IEC ball pressure test value is 210 °C.
- Dimensional stability
In contrast to similar applications based on polyamide, Pocan[®] B 4215 does not absorb water, which gives it a very high level of dimensional stability.
- Rheological properties
Glass fiber-reinforced Pocan has a particularly high level of flowability, which allows long flow paths and complex geometries.



DEHNguard® is a registered trade name of DEHN + SÖHNE GmbH + Co. KG.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Trial Products (grade designations beginning with the codes DP, TP, KL or KU)

This is a Sales Product at the developmental stage (a Trial Product). For this reason, no assurances can be given as to type conformity, processability, long-term performance characteristics or other production or application parameters. No definitive statements can be made regarding the behavior of the product during processing or use. The purchaser/user uses the product entirely at his own risk. The marketing and continued supply of this material are not assured and may be discontinued at any time.

© = LANXESS Deutschland GmbH 2008, SCP Business Unit | all rights reserved

www.pocan.com

Page 2 of 2, Edition 06.03.2008, TI 2006-039

